



Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 2G Superior click system
Description	Plank Size 7" Wide x 48" Long (Wood Grain Texture)
Size / Thickness	4.7mm Total Thickness (3.7mm Core + 1.0mm EVA) 12 mil Wearlayer
Quality	1st quality, natural color variation, free of structural defects
Installation	2G Click System - Floating
Warranty	Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty
Wear Resistance (EN13329)	≥ 4000 cycles - Classification (Class 34)
Impact Resistance (EN13329)	≥ 1800mm - Classification (Class 34)
Micro-scratch Resistance	ISO 1518-1 - ≥ 3200g
Static Load (250>BS/115KG)	ASTM F970 - 15 - Class 4 Heavy Commercial
Impact Sound Reduction (IIC)	IIC: 59
Locking Strength	Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m
Resistance to staining	No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H ₂ O ₂), shoe polish.
Fire Resistance	ASTM E648/662 - 1.09 W/cm ² - Class 1
Fungi Resistance ASTM G21-15	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore®	SCS-FS-04026 2020.06.01 - 2021.05.31
Packaging	
Content of Box	(7" x 48" - 21.27 Sq.Ft./ Box)
Content of Pallet	(65 cartons - 2149.50 lbs)